



Text for Invitation to Tender ABS-Lock® Falz III System:

Roof Anchorage Point in Accordance with EN 795, Class A

ABS-Lock® Falz III aluminum safety bracket, with freely-rotating stainless steel anchor eyelet. Unobtrusive to the eye due to its small size, no negative impact on the general roof picture. Simple and quick installation using a clamp, no roof penetration necessary, suitable for all rounded-edge seams, such as Kalzip, Bemo, Interfalz etc. Low-cost roof anchorage point for 1 individual. The supports can be positioned up to 7.5 m apart.

<u>Pos.</u>	<u>Description</u>	<u>Quantity</u>	<u>PPU</u>	<u>TOTAL</u>
	ABS-Lock® Falz III	_____	_____	_____ €

PPE set, CE-tested, consisting of:

Safety cable ABS ASK8 14mm x 23m sharp-edge protected kernmantle cable with 2 freely-moving carabiner hooks and rope shortener, designed for hooking onto ABS-Lock® Falz III roof anchorage points.

Connector cable up to 15m in length, including a rope shortener and force absorber, designed for work carried out near precipitous edges.

Safety harness, protective bag

<u>Pos.</u>	<u>Description</u>	<u>Quantity</u>	<u>PPU</u>	<u>TOTAL</u>
	ABS PPE Set	_____	_____	_____ €
	ABS ASK 8	_____	_____	_____ €

ABS Safety GmbH

Gewerbering 3

47623 Kevelaer

Germany

Tel.: 0049 (0) 2832 97281-0

Fax: 0049 (0) 2832 97281-29

info@fall-arrest.eu

www.fall-arrest.eu