

PROJECT DETAILS



ADDRESS/ CLIENT

Project / Company

Street No.

Zip City

Contact Person

Telephone Fax

E-Mail

ADDRESS (PROJECT)

Company

Street No.

Zip City

Type of Height Safety

- Safety Guardrail
- Single Point Anchor
- Non-traversable Lifeline System
- Traversable Lifeline System

Building height (m)

Fall distance (m)

min.

max.

Access

- Ladder
- Stairs
- Cherry Picker
- Skylight
- Cat Ladder
-

Roof Surface

- Plastic Membrane
Brand:
- Bitumen
- Standing Seam
- Trapezoidal
- Sandwich
- Gravel ____ mm height
- Green Roof ____ mm height
-

Roof Slope

- 0 - 5°
- 6 - 15°
- 16 - 25°
- 26 - 45°
- > 45°

Mounting Surface

- Concrete
- Light Concrete
- Prestressed concrete
- Wood Casing
- Wood Rafter
- Steel Beam
-

Insulation Thickness

- 100 mm
- 200 mm
- 300 mm
- 400 mm
- 500 mm
-

Penetration Sealing Sheet

- Possible
- Impossible

Skylights permanently shockproof

- Yes
- No

Roof Sketch

Please provide necessary information:
Dimensioning, Roof Edge, Skylight, Luminaires, Roof Construction