

## Tender Text: ABS Lock X-T-ALU

### Stainless steel fall protection anchor in accordance with EN 795

Anchorage ABS-Lock X-T-ALU, d=16mm , force absorbing through plastic deformation, for mounting directly onto sandwich panels (starting at 0,7mm) installation material included (special toggle bolts). Completely made from stainless steel, with detachable eyelet, support distances up to max. 7,5 m. Minimum distance to the roofs edge 2,5m, needs to be installed according to the manufacturers instructions and with the supplied installation material. It needs to be insulated according to the flat roof regulations. It needs to be checked by the customer whether the roof can withstand the forces that will be applied in case of a fall.

Pos.	Description	Amount	EP	GP
xxx	ABS-Lock X-T-ALU (o.glw.)	x	x	x

Matching personal protective equipment is available though this link:

[http://www.fall-arrest.eu/ppe-fall-protection/ppe\\_sets\\_personal\\_fall\\_protection\\_equipment.html#!/Product+Description](http://www.fall-arrest.eu/ppe-fall-protection/ppe_sets_personal_fall_protection_equipment.html#!/Product+Description)

ABS Safety GmbH  
Gewerbering 3  
47623 Kevelaer  
Tel.: 0049 (0) 2832 97281-0  
Fax.: 0049 (0) 2832 97281-29  
[info@fall-arrest.eu](mailto:info@fall-arrest.eu)  
[www.fall-arrest.eu](http://www.fall-arrest.eu)