

CLIENT'S ADDRESS

Project/Company	
Street	No.
Postcode	City
Contact	
Telephone	Fax
Email	

PROJECT ADDRESS

Company	
Street	No.
Postcode	City

Stepladder / Stepladder with a 60° platform

1. Stepladder height

<input type="text"/>	mm
----------------------	----

2. Plattformlänge (mm)

<input type="checkbox"/>	600 mm
<input type="checkbox"/>	800 mm
<input type="checkbox"/>	1000 mm
<input type="checkbox"/>	None

3. Material of the supporting structure (wall installation)

<input type="checkbox"/>	Concrete	
<input type="checkbox"/>	Wood	
<input type="checkbox"/>	Steel	
<input type="checkbox"/>	Masonry	
<input type="checkbox"/>	Porous concrete elements (autoclaved aerated concrete)	Depth ____ mm
<input type="checkbox"/>	Thermal insulation (EIFS)	Depth ____ mm
<input type="checkbox"/>	Rainscreen	Depth ____ mm
<input type="checkbox"/>	Metal facade	Depth ____ mm
<input type="checkbox"/>	Insulated sandwich panels	Depth ____ mm

4. Would you like us to install the stepladder?

<input type="checkbox"/>	Yes
<input type="checkbox"/>	No

5. Would you like us to inspect the stepladder and document this accordingly?

Stepladders need to be inspected regularly to ensure that they are in good working condition. These inspections are conducted in accordance with DGUV Publication 208-005, the German Workplaces Ordinance (ArbStättV), the German Ordinance on Industrial Safety and Health (BetrSichV) and the German Act on the Implementation of Measures of Occupational Safety and Health (ArbSchG).

<input type="checkbox"/>	Yes
<input type="checkbox"/>	No

Notes:

- According to EN ISO 14122-3, stepladders must have handrails on both sides. Stepladders with a platform need to be fitted with handrails on both sides as well as a guard rail.
- All ABS stepladders and stepladders with a platform are supplied with feet and an upper bracket and have to be fixed to the ground and supporting structure.
- ABS stepladders and stepladders with a platform are equipped with aluminium grated steps and platforms that provide extra slip resistance in accordance with DIN 51130 (slip resistance rating R13).
- The length of an individual stepladder section must not exceed 3000 mm!