ABS-Lock Falz IV Klip

Anchorage point - designed for clamping permanently onto metal seams



Our stainless steel ABS-Lock Falz IV Klip is simply clamped onto two adjacent metal seams (e.g. KlipTec, Snapfalz etc.) to protect 3 individuals from falls. This is achieved using special aluminium clamps that avoid opening up your roof membrane. Once the clamps have been professionally installed, the anchor sits firmly on top of the roof membrane.

You can implement this anchorage device either as a single anchorage point or as a load-bearing intermediate element in a lifeline system, depending on your requirements. Our ABS-Lock Falz IV Klip can easily cope with the pre-tensioning load exerted on the stainless steel cable. A fully traversable lifeline system offers the ultimate in user-friendliness and an uninterrupted workflow: Secure your whole roof surface absolutely interruption-free, e.g. through the implementation of an ABS-Lock SYS IV system. Your workers only need to hook up once and can then use their matching gliders to move along parallel to the system without encountering any obstructions - and without needing to unhook/rehook.

- EN 795:2012, A CEN/TS 16415:2017
- Clamped onto two adjacent seams - completely penetration-free
- Seam intervals: 300 - 450 mm / 420 - 660 mm
- Sheet thickness ≥ 0.75mm
- e.g. KlipTec, Snapfalz or similar
- Incl. installation set
- We also supply a protruding model for use in a lifeline system

Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH

fon: 49 2832 – 97281-0
fax: 49 2832 – 97281-29

info@absturzsicherung.de
www.absturzsicherung.de



Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH

fon: 49 2832 – 97281-0
fax: 49 2832 – 97281-29

info@absturzsicherung.de
www.absturzsicherung.de