

# ABS-Lock Falz V Rounded Seam

Anchorage point - designed for clamping onto metal seams



Our ABS-Lock Falz V Rounded Seam single anchorage point includes a freely rotating anchorage eyelet for maximum manoeuvrability on a metal seam roof. This fall protection device is simply clamped onto a rounded-edge seam (e.g. BEMO etc.) using specially designed aluminium clamps - totally penetration-free.

As you only need one single seam to install this system, the distance between the seams is totally irrelevant. Once professionally installed, the device is suitable for usage by 3 individuals equipped with matching personal fall protection equipment (PPE). Our range of Fall arrest PPE products offers all the components you need, such as safety harnesses and lanyards.

## Certification

EN 795

## Force Directions

Lateral

## Substructure

Seam roofs      Profile Roof

## Max. no. of users

3 Persons

## Miscellaneous

360° Rotating      Stainless Steel

## Attachment

clamped      w/o roof penetration

## Application

Profile Roof      Flat Roofs

- EN 795:2012, A + CEN/TS 16415:2013
- Completely penetration-free installation
- Mounted on a single seam
- Aluminium depth  $\geq 0.7$  mm
- For BEMO and similar systems



Gewerbering 3 · D-47623 Kevelaer  
ABS Safety GmbH



fon: +49 2832 – 97281-0  
fax: +49 2832 – 97281-29



info@absturzsicherung.de  
www.absturzsicherung.de

