

ABS-Lock Falz V Standing Seam

Anchorage point - designed for clamping onto metal seams



Our ABS-Lock Falz V Standing Seam offers you a single anchorage point capable of securing up to 3 individuals working on a metal seam roof. The device is simply clamped onto a single standing seam - for maximum ease of usage: The stainless steel eyelet rotates a full 360°. This anchorage device is suitable for standing seam roof solutions offered by a range of different manufacturers, e.g. Rheinzink and similar systems.

Our anchor protects roof workers near a precipitous edge and in areas where there is an increased danger of falling (e.g. in the vicinity of a domed rooflight). The special clamping mechanism provides reliable support and is also kind to your roof membrane: There is no need to open up your roof or drill through it.

Substructure

Seam roofs Profile Roof

Application

Profile Roof Flat Roofs

Attachment

clamped

Certification

EN 795

Force Directions

Lateral

Max. no. of users

3 Persons

Miscellaneous

Stainless Steel 360° Rotating

- EN 795:2012, A + CEN/TS 16415:2013
- Freely-rotating anchor eyelet
- Clamped onto a seam without penetrating your roof surface
- Mounted on a single seam
- For Rheinzink and similar systems



Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH



fon: +49 2832 – 97281-0
fax: +49 2832 – 97281-29



info@absturzsicherung.de
www.absturzsicherung.de

