# ABS-Lock X-SR-ST

Anchorage point for steel structures - countered

**Substructure**
Steel

**Application**
Flat Roofs

**Attachment**
countered

**Certification**
EN 795 DIBt Approval | Ü-Sign

**ABS-Lock SYS**
HLL Intermediate End and corner support

**Force Directions**
Lateral and Axial

**Max. no. of users**
3 Persons

**Miscellaneous**
Abseiling suitable (1 individual) Stainless Steel

Do you require a single anchorage point with a protrusion of 400, 700 or 1000 mm? No problem! Our ABS-Lock X-SR-ST is just what you are looking for. This anchor is available in standard lengths, starting at 300 mm and going up to 1000 mm in 100 mm steps. As the anchor device is equipped with a welded-on supporting tube which is countered after installation on a steel structure, it offers a really powerful fall arrest solution capable of securing three individuals simultaneously.

The reinforced ABS-Lock X-SR-ST rod sits on top of a stainless steel base plate - just perfect for use as a supporting element in a lifeline system. The base plate is attached to a steel substructure using 4 nuts and bolts. These are then countered on the opposite side. This design can easily cope with the pre-tensioning load exerted on your lifeline system. A variety of different rod lengths allow you to flexibly plan your lifeline system to suit your individual needs. Our experienced Planning Team would be more than happy to be of assistance.

When designing your lifeline solution, all the options are open to you: Ground, wall or overhead installation; fully traversable; based on a 6 or 8 mm stainless steel cable. Click here for an overview of all our lifeline and rail safety systems.

- National technical approval ("abZ"): Z-14.9-688
  (pls. observe the installation instructions provided in the "abZ")
- EN 795:2012, A + CEN/TS 16415:2017
- Base plate + welded-on supporting tube
- Incl.stainless steel installation set

Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH

fon: +49 2832 – 97281-0
fax: +49 2832 – 97281-29

info@absturzsicherung.de
www.absturzsicherung.de

**ABS-Lock X-SR Extension**
Extension for an ABS-Lock X-SR anchorage point

Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH

fon: +49 2832 – 97281-0
fax: +49 2832 – 97281-29

info@absturzsicherung.de
www.absturzsicherung.de