ABS-Lock X-SR Extension

Extension for an ABS-Lock X-SR anchorage point

To provide a high level of stability when used in a lifeline system, our ABS Safety anchorage points are also available with a welded-on supporting tube to cope with most subsurfaces. The extra-strong rod (Ø 42 mm) can easily handle the level of pre-tensioning required in a lifeline system. This means that these anchors can also be used as supports at the corners or end terminals which are subjected to a particularly high load.

No problem, if you want to extend an ABS-Lock X-SR anchorage point or system support - simply screw an ABS-Lock X-SR Extension on top of the rod to extend it by an additional 100 or 200 mm. All the required installation materials are included with this high-quality, stainless steel extension, as well as a plastic energy absorber and an easy-to-follow installation manual. Should you have any questions regarding extending an ABS Safety anchorage point, please either call us or send us an email. Feel free to contact our Sales Team at any time!

- EN 795:2012, A
- CEN/TS 16415:2013
- Available in two lengths: 100 mm and 200 mm
- Energy absorber included
- Installation materials supplied

Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH

fon: 49 2832 – 97281-0
fax: 49 2832 – 97281-29

info@absturzsicherung.de
www.absturzsicherung.de

Gewerbering 3 · D-47623 Kevelaer
ABS Safety GmbH

fon: 49 2832 – 97281-0
fax: 49 2832 – 97281-29

info@absturzsicherung.de
www.absturzsicherung.de