

## ABS Dome OnTop Fusion

Guard rail for domed rooflights - designed for fusing onto bitumen and fabric-reinforced plastic membranes



Our ABS Dome OnTop Fusion guard rail offers penetration-free fall protection around domed rooflights. You will not require any additional weights when installing our new ABS Safety guard rail system as it is simply fused onto a bitumen or fabric-reinforced plastic membrane surface. Once it has been set up, cover the feet of our ABS Dome OnTop Fusion guard rail with squares of roof membrane material. Then simply fuse these onto the roof membrane surface.

As this system is really lightweight and easy to handle, you will not have any problems getting it up onto your roof. Our ABS Dome OnTop Fusion guard rail is tested and certified in accordance with EN 13374:2013. It is suitable for flat roofs with a maximum pitch of 10°.

---

**Certification****Substructure**

Bitumen / Plastic Membrane

**Max. no. of users****Attachment**

fused

**Application**

Guardrail systems      Flat Roofs

**Miscellaneous**

Additional Shipping Costs

- EN 13374:2013, A
- Designed for flat roof pitches  $\leq 10^\circ$
- Suitable for domed rooflights: Max. 2.5 m x 2.5 m
- Handrail height: 1100 mm
- Weight per post: Approx. 3 kg (traditional posts 30 kg)
- Set includes bitumen patches
- PVC patches need to be provided and cut to size onsite



## Accessories / Components

